

Bachman Services, Inc.
2220 S. Prospect
Oklahoma City, OK 73143

Emergency Response: 800-535-5053
Information: 405-677-8296

MATERIAL SAFETY DATA SHEET

1. Chemical Identification

Product: **BachCide 320**
General Description: E.P.A. Registered Biocide
Chemical Family: THPS
Revision Date: July 13, 2011
Primary Hazard: Combustible Liquid
RQ Component

Hazard Rating		Rating Scale
Health	2	4 = Extreme
Fire	2	3 = High
Reactivity	0	2 = Moderate
Personal Protection	B	1 = Slight
		0 = Insignificant

2. Hazardous Ingredients

Our hazard evaluation has identified the following chemical ingredient(s) as hazardous. One or more component is being claimed as a trade secret under OSHA's Hazard Communication Rule, 29 CFR 1910.1200. Consult section 14 for the nature of the hazard(s).

Ingredient(s)	CAS Number	Approximate Wt. %
Methanol	67-56-1	15

3. Handling Precautions

DANGER! Combustible Liquid. Contains methanol. May cause blindness if swallowed. May be harmful if inhaled. Do not use, store, spill or pour near heat, sparks or open flame. Keep container closed when not in use. Use with adequate ventilation. Do not take internally. Avoid prolonged or repeated breathing of vapor. Avoid contact with skin, eyes or clothing. Empty containers may contain residual product. Do not reuse container unless properly reconditioned.

4. First Aid Information

EYES: Remove victim from exposure and into fresh air. Immediately flush with water for at least 15 minutes while holding eyelids open. Call a physician at once.

SKIN: Remove contaminated clothing. Immediately wash exposed area with soap and water for at least 15 minutes. For a large splash flood body under a shower. Call a physician at once. Launder clothes before reuse.

INGESTION: If victim is conscious and alert, induce vomiting by giving syrup of ipecac or by gently stimulating victim's uvula. Give water. Call a physician at once. If victim is drowsy or unconscious, do not induce vomiting or give anything by mouth; place victim on the left side with the head down. If possible, do not leave victim unattended.

INHALATION: Remove to fresh air. If breathing is difficult, administer oxygen. Treat symptoms. Keep victim warm and quiet. Seek immediate medical attention.

CAUTION: If unconscious, having trouble breathing or in convulsions, do not induce vomiting or give water.

Note To Physicians

This product contains methanol. Ethanol decreases the metabolism of methanol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning. If ethanol therapy is indicated, administer a loaded dose of 7.6 to 10 mL of 10% ETOH in D5W over 30 – 60 minutes. Maintenance dose of 1.4 mL/Kg/Hr of 10% ETOH, to achieve a 100 to 130 mg/dL blood ETOH level during ethanol therapy. (If charcoal is administered, ethanol should be administered intravenously and not orally.)

5. Health Effects Information

Primary Route(s) Of Exposure: Eye, Ingestion, Inhalation, Skin

Eye Contact: Irritating to the eyes with possible permanent damage depending on the length of exposure and on the first aid action given. Symptoms may include stinging, tearing, redness and swelling.

Skin Contact: Irritating to the skin. Symptoms may include redness and burning. Skin adsorption possible, but harmful effects are not expected from this route of exposure under normal conditions of handling and use. Can cause allergic contact dermatitis in susceptible individuals.

Ingestion: Can cause blindness due to methanol. Ingestion of this product will also cause severe abdominal distress, with nausea, vomiting and diarrhea probable depending on the first aid action given. See note to physician, above.

Inhalation: Prolonged inhalation of mist or vapor in excess of the recommended exposure limits can be harmful, causing nausea, irritation, dizziness, light-headedness, vomiting, fatigue, headache or unconsciousness depending on the length of exposure and the first aid action given.

Symptoms

Of Exposure: A review of available data does not identify any symptoms from exposure not previously mentioned.

Aggravation Of Existing Conditions: A review of available data does not identify any worsening of existing conditions.

6. Toxicological Information

Toxicity Studies: No toxicity studies have been conducted on this product. However, this product contains methanol. Ingestion of methanol, even in small amounts, can cause blindness and death. This material is not listed as a carcinogen by IARC, NTP or OSHA.

7. Physical & Chemical Properties

Appearance:	Clear, Amber Liquid	Pour Point:	-20°F
Odor:	Alcohol	Initial Boiling Point:	147 °F
Specific Gravity:	1.055	Flash Point:	54 °F TCC
Density:	8.80	Vapor Pressure:	96 mm HG @ 100 °F
pH (neat):	3.0 – 4.0	Vapor Density:	> 1.0 (Air = 1.0)
Viscosity:	4 cst @ 100°F	Evaporation Rate:	3.5 (Butyl Acetate = 1.0)
Solubility:	Water Soluble		

Note: These physical properties are typical values for this product and not specifications.

8. Fire & Explosion Information

Flash Point: 54°F
Lower Explosive Limit: 2.0%
Upper Explosive Limit: 36.0%

Extinguishing Media: Based on NFPA guide, use water fog, dry chemical, foam, carbon dioxide or other extinguishing agent suitable for Class B fires. Use water to cool containers exposed to fire. For large fires, use water spray or fog, thoroughly drench the burning material.

Unusual Fire And Explosion Hazards: May evolve CO, CO₂ and/or NO_x under fire conditions. Containers exposed in a fire should be cooled with water to prevent vapor pressure buildup leading to rupture.

9. Reactivity Information

Incompatibility: Avoid contact with strong oxidizers (eg. chlorine, peroxides, chromates, nitric acid, perchlorates, concentrated oxygen, permanganates) which can generate heat, fires, explosions and the release of toxic fumes.

Thermal Decomposition Products: In the event of combustion CO, CO₂ and/or NO_x may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment.

10. Personal Protection Equipment

Respiratory Protection: If it is possible to generate significant levels of vapors or mists, a NIOSH approved or equivalent respirator is recommended. For large spills, entry into large tanks, vessels or enclosed small spaces with inadequate ventilation, a positive pressure, self-contained breathing apparatus is recommended.

Ventilation: General ventilation is recommended. Additionally, local exhaust ventilation is recommended where vapors, mists or aerosols may be released.

Protective Equipment: Wear impermeable gloves, boots, apron and face shield with chemical splash goggles. A full slicker suit is recommended if gross exposure is possible.

The availability of an eye wash fountain and safety shower are recommended. If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse.

11. Spill & Disposal Information

In case of transportation accident, call the emergency response phone number: 800-535-5053

Spill Control And Recovery:

Small Spills: Contain with absorbent material, such as clay, soil or any commercially available absorbent. Shovel reclaimed liquid and absorbent into recovery or salvage drums for disposal. Refer to CERCLA in Section 14.

11. Spill & Disposal Information (continued)

Large Spills: Dike and prevent further movement and reclaim into recovery or salvage drums or tank truck for disposal. Refer to CERCLA in Section 14.

For large indoor spills, evacuate employees and ventilate area. Eliminate all sources of spark or flame. Those responsible for control and recovery should wear the protective equipment specified in Section 10. Ventilate area and evacuate employees from exposure if the airborne concentration exceeds the TLV. Refer to Section 14.

Prevent flow/discharge into lakes, ponds, streams, waterways or public water supplies.

Disposal: If this product becomes a waste, it meets the criteria of a hazardous waste as defined under the Resources Conservation and Recovery Act (RCRA) 40 CFR 261. Hazardous Waste D001.

As a hazardous liquid waste, it must be solidified with stabilizing agents (such as sand, fly ash, or cement) so that no free liquid remains before disposal to a licensed industrial waste landfill (Hazardous Waste Treatment, Storage and Disposal facility). A hazardous liquid waste can also be incinerated in accordance with local, state and federal regulations.

12. Environmental Information

If released into the environment, see CERCLA in Section 14.

13. Transportation Information

The proper shipping name and/or hazard class for this product may vary according to packaging, properties and mode of transportation. Typical proper shipping names for this product are:

Drums & Pails:	Not D.O.T. Regulated
Totes & Bulk:	Combustible Liquid, N.O.S.
UN/ID Number:	NA-1993
Hazard Class:	3, Combustible Liquid
Packing Group:	III
Flash Point:	54°F
Hazardous Components:	Methanol
RQ lbs:	7,333
RQ Component(s):	Methanol

14. Regulatory Information

The following regulations apply to this product:

Federal Regulations:

OSHA's Hazard Communication Rule, 29 CFR 1910.1200:

Based on our hazard evaluation, the following ingredients in this product are hazardous and the reasons are shown below.

Methanol – Flammable, Systemic effects (refer to Section 5)

14. Regulatory Information (continued from page 5)

Clean Air Act, Sec 111 (40 CFR60), Sec 112 (40 CFR 61, 1990 Amendments), Sec 611 (40 CFR 82, Class I and II Ozone Depleting Substances):

None of the ingredients of this product are covered by the Clean Air Act.

State Regulations:

California Proposition 65:

This product does not contain any chemicals which require warning under California Proposition 65.

Michigan Critical Materials:

This product does not contain any ingredients listed on the Michigan Critical Materials Register.

State Right To Know Laws:

This product is regulated in those states using the TLV for methanol as a criteria for listing.

15. User's Responsibility

The information accumulated herein is believed to be accurate based on the information provided, although no guarantee or warranty, either expressed or implied is made as to the accuracy or completeness of this information, whether originating with this company or not. Recipients are advised to confirm in advance of need that the information is correct, applicable and suitable to their circumstances. The conditions or methods of handling, storage, use and disposal of the product and container are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage or use of this information or product. If the product is used as a component in another product, this information may not be applicable.

Prepared By: L.V. Robertson
Original Date: February 6, 2003