

Material Safety Data Sheet: DYNASOLVE AEROSOL

Supersedes Date 19-Oct-2004

Issuing Date 14-Apr-2008

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name DYNASOLVE AEROSOL
Recommended Use solvent
Information on Manufacturer
 Partsmaster, Div of NCH Corp.
 P.O. Box 655326
 Dallas, TX 75265-5326

Product Code 5491
Chemical Nature Solvent mixture
Emergency Telephone Number
 CHEMTREC® 800-424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview
 Danger
 Extremely flammable
 May be harmful if inhaled
 Causes skin irritation
 Causes eye irritation
 May cause allergic skin reaction
 May cause allergic respiratory reaction
 Harmful or fatal if swallowed

Color Colorless	Physical State Liquid	Odor orange
Potential Health Effects	Skin contact, Eye contact, Inhalation.	
Principle Route of Exposure	Inhalation, Skin Absorption.	
Primary Routes of Entry		
Acute Effects		
Eyes	Causes eye irritation.	
Skin	Causes skin irritation. May cause allergic skin reaction.	
Inhalation	May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause headache and dizziness. May cause allergic respiratory reaction.	
Ingestion	Ingestion may cause irritation to mucous membranes. Aspiration hazard if swallowed - can enter lungs and cause damage.	
Chronic Effects	May cause skin sensitization in some individuals . May cause respiratory sensitization in some individuals .	
Target Organ Effects	Bone Marrow, Lungs, Central nervous system.	
Aggravated Medical Conditions	Skin disorders. Respiratory disorders.	
Potential Environmental Effects	See Section 12 for additional Ecological information	

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No
Butane	106-97-8
D-Limonene	5989-27-5
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	64741-66-8
Propane	74-98-6

The product contains no substances which at their given concentration, are considered to be hazardous to health

4. FIRST AID MEASURES

General Advice	Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing.
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Inhalation	Move to fresh air. In case of shortness of breath, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.
Ingestion	Drink 1 or 2 glasses of water. Do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
Notes to Physician	Aspiration hazard if swallowed - can enter lungs and cause damage.

5. FIRE-FIGHTING MEASURES

Flash Point 39°F / 4°C	Method Seta closed cup
Autoignition Temperature No information available	
Flammability Limits in Air Solvent mixture	Upper 9.5 Lower 0.7
Suitable Extinguishing Media	
Water spray. Carbon dioxide (CO2). Foam. Dry chemical.	
Specific Hazards Arising from the Chemical	
Flame extension: >30 inches / >76 cm and Burnback: 5 inches / 13 cm	
. Solvent vapors are heavier than air and may spread along floors . Vapors may ignite and explode.	
Protective Equipment and Precautions for Firefighters	
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.	
NFPA	Health 1 Flammability 4 Instability 0

HMIS Health 1 Flammability 4 Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Prevent further leakage or spillage if safe to do so.
Environmental Precautions Do not flush into surface water or sanitary sewer system.
Methods for Containment No information available
Methods for Cleaning Up Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Neutralizing Agent Not applicable

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist or gas.
Storage Keep away from heat and sources of ignition.
Storage Temperature **Minimum** 35°F / 2°C **Maximum** 120°F / 49°C
Storage Conditions **Indoor X** **Outdoor** **Heated** **Refrigerated**

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Butane	TWA: 1000 ppm	no data available	TWA: 1900 mg/m ³ TWA: 800 ppm
D-Limonene	No data available	no data available	no data available
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	No data available	no data available	no data available
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1800 mg/m ³ TWA: 1000 ppm

Engineering Measures Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment
Eye/Face Protection Safety glasses with side-shields.
Skin Protection Impervious gloves.
Respiratory Protection Use NIOSH approved respiratory protection.
General Hygiene Considerations Ensure that eyewash stations and safety showers are close to the workstation location. Wear protective gloves/clothing. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Viscosity	Non viscous
Color	Colorless	Odor	orange
Appearance	Transparent	pH	Not applicable
Specific Gravity	0.77	Bulk Density	No data available
Evaporation Rate	37.4	Percent Volatile (Volume)	100
VOC Content (%)	100	Vapor Pressure	1950 mmHg @ 70 °F
Vapor Density	1.7	Solubility	Insoluble
Boiling Point/Range	340°F / 171°C		

10. STABILITY AND REACTIVITY

Chemical Stability Stable. Hazardous polymerization does not occur .
Conditions to Avoid Heat, flames, and sparks.
Incompatible Products Strong oxidizing agents. Acids. Vinyl compounds. Halogenated hydrocarbon.
Hazardous Decomposition Products Carbon oxides.
Possibility of Hazardous Reactions None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information No information available

Acute Toxicity

Component Information

Acute toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Butane	no data available	no data available	658 g/m ³ (Rat) 4 h	no data available	no data available
D-Limonene	4400 mg/kg (Rat)	2000 mg/kg (Rabbit)	no data available	no data available	no data available
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	7000 mg/kg (Rat)	2000 mg/kg (Rabbit)	5.04 mg/L (Rat) 4 h	no data available	no data available
Propane	no data available	658 mg/kg (Rat)	no data available	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Butane	no data available	no data available	no data available	no data available	CNS
D-Limonene	no data available	Skin sensitization Respiratory sensitizer	no data available	no data available	CNS, bone marrow, lungs

Naphtha (petroleum)light alkylate (<3% DMSO extractable)	no data available	no data available	no data available	no data available	CNS
Propane	no data available	no data available	no data available	no data available	CNS

Carcinogenicity There are no known carcinogenic chemicals in this product

Component	ACGIH	IARC	NTP	OSHA	Other
Butane	not applicable	not applicable	not applicable	not applicable	not applicable
D-Limonene	not applicable	not applicable	not applicable	not applicable	not applicable
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	not applicable	not applicable	not applicable	not applicable	not applicable
Propane	not applicable	not applicable	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information No information available

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Butane	no data available	no data available	no data available	no data available	2.89
D-Limonene	no data available	LC50= 702 mg/L Pimephales promelas 96 h	no data available	no data available	N/A
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	EC50= 30000 mg/L Selenastrum capricornutum 72 h	no data available	no data available	LC50 = 2 mg/L 48 h	N/A
Propane	no data available	no data available	no data available	no data available	2.3

Persistence and Degradability No information available

Bioaccumulation No information available

Mobility No information available

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of as hazardous waste in compliance with local and national regulations

Container Disposal Contents under pressure Do not puncture. Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT	DOT
Proper Shipping Name	Consumer commodity
Hazard Class	ORM-D
Description	Consumer commodity ,ORM-D,
TDG	
Proper shipping name	Aerosols
Hazard Class	2.1
UN-No	UN1950
Description	AEROSOLS,2.1,UN1950 LTD QTY
ICAO	
UN-No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Shipping Description	Aerosols,UN1950 LTD QTY
IATA	
UN-No	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1
ERG Code	10L
Shipping Description	UN1950,Aerosols, flammable,2.1 LTD QTY
IMDG/IMO	
Proper Shipping Name	Aerosols
Hazard Class	2.1
UN-No	UN1950
EmS No.	F-D, S-U
Shipping Description	UN1950, Aerosols,2.1 LTD QTY

15. REGULATORY INFORMATION

Inventories

TSCA Complies

DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the

reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute Health Hazard Yes	Chronic Health Hazard Yes	Fire Hazard Yes	Sudden Release of Pressure Hazard Yes	Reactive Hazard No
-----------------------------------	-------------------------------------	---------------------------	---	------------------------------

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Butane	Not applicable	Not applicable
D-Limonene	Not applicable	Not applicable
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	Not applicable	Not applicable
Propane	Not applicable	Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

A Compressed gases, B5 Flammable aerosol, D2B Toxic materials .



16. OTHER INFORMATION

Prepared By	Mike McDowell
Supercedes Date	19-Oct-2004
Issuing Date	14-Apr-2008
Reason for Revision	No information available
Glossary	No information available
List of References	No information available

Partsmaster, Div of NCH Corp. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.