

MATERIAL SAFETY DATA SHEET

1. Chemical Identification

Product: **PCO-5450**
General Description: Paraffin Solvent
Chemical Family: Blend
Revision Date: January 17, 2011
Primary Hazard: Flammable Liquid
RQ Components

Hazard Rating		Rating Scale
Health	3	4 = Extreme
Fire	3	3 = High
Reactivity	0	2 = Moderate
Personal Protection	B	1 = Slight
		0 = Insignificant

2. Hazardous Ingredients

Our hazard evaluation has identified the following chemical ingredient(s) as hazardous. One or more component is being claimed as a trade secret under OSHA's Hazard Communication Rule, 29 CFR 1910.1200. Consult section 14 for the nature of the hazard(s).

Ingredient(s)	CAS Number	Approximate Wt. %
Carbon Disulfide	75-15-0	Confidential
Xylene	1330-20-7	20
Isopropanol	67-63-0	5
Light Hydrocarbon	8008-20-6	15

3. Handling Precautions

DANGER! Flammable Liquid. Causes irritation/burns to the skin, eyes and respiratory tract. May be absorbed through skin. Avoid contact with skin, eyes and clothing. Avoid prolonged or repeated breathing of vapor. Do not use, store, spill or pour near heat, sparks or open flame. Keep container closed when not in use. Use with adequate ventilation. Do not take internally. Empty containers may contain residual product. Do not reuse container unless properly reconditioned.

4. First Aid Information

EYES: Remove victim from exposure and into fresh air. Immediately flush with water for at least 15 minutes while holding eyelids open. If victim is wearing contact lenses, remove before flushing eyes with water if possible. Call a physician at once.

SKIN: Remove contaminated clothing. Immediately wash exposed area with soap and water for at least 15 minutes. For a large splash flood body under a shower. Call a physician at once. Launder clothes before reuse.

INGESTION: Do not induce vomiting. Give water. Call a physician at once. If possible, do not leave victim unattended.

INHALATION: Remove to fresh air. If breathing is difficult, administer oxygen. Treat symptoms. Keep victim warm and quiet. Seek immediate medical attention.

CAUTION: If unconscious, having trouble breathing or in convulsions, do not induce vomiting or give water.

Note To Physicians

Based on individual reactions of the patient, the physician's judgment should be used to control symptoms and clinical condition.

5. Health Effects Information

Primary Route(s) Of Exposure: Eye & Skin Contact, Skin Absorption, Inhalation

Eye Contact: Can cause severe eye irritation and burns with possible permanent damage depending on the length of exposure and on the first aid action given. Symptoms may include stinging, tearing, redness and swelling.

Skin Contact: Can cause severe skin irritation and blistering depending on the length of exposure and on the first aid action given. This product contains carbon disulfide, which is readily absorbed through the skin. Nerve damage near the site of absorption may result. Skin absorption can produce symptoms similar to those of inhalation.

Ingestion: Can cause burns to the mouth, throat, esophagus and stomach. Swallowing of product may cause central nervous system depression, abdominal distress, with nausea, vomiting, diarrhea reduction of blood pressure, unconsciousness and death depending on the length of exposure and the first aid action given.

Inhalation: Inhalation of mist or vapor can be harmful, causing headache, nausea, irritation, dizziness, light-headedness, vomiting, fatigue, or unconsciousness depending on the length of exposure and the first aid action given.

Symptoms

Of Exposure: **ACUTE:** A review of available data does not identify any symptoms from exposure not previously mentioned.

CHRONIC: Prolonged skin contact can cause dry skin and defatting resulting in irritation and dermatitis. See Section 6 for additional information.

Aggravation Of Existing Conditions: A review of available data does not identify any worsening of existing conditions.

6. Toxicological Information

Toxicity Studies: No toxicity studies have been conducted on this product. However, this product contains heavy aromatic naphtha which may contain polynuclear aromatic hydrocarbons (PNA's). Studies have shown that the repeated painting of PNA's on the skin of experimental animals over a sustained period of time results in the induction of tumors. Individuals should avoid skin contact and should wash affected areas immediately if contact occurs.

This product contains carbon disulfide which has been found to cause reproductive, neurologic and cardiac effects following repeated or prolonged inhalation exposure. Over exposure to carbon disulfide may effect the skin, eyes, respiratory system, peripheral and central nervous system, cardiovascular system and reproductive system.

This product also contains isopropanol. In concentrated form, this chemical has been reported in one animal study to be fetotoxic at levels of 2.5% in drinking water. No tetragenic effects were, or have been reported. There are no reports of adverse reproductive effects in humans exposed to this chemical.

7. Physical & Chemical Properties

Appearance:	Clear, Red Liquid	Pour Point:	-40°F
Odor:	Sulfur	Initial Boiling Point:	180 °F
Specific Gravity:	1.044	Flash Point:	<10 °F TCC
Density:	8.71	Vapor Pressure:	9.5 mm HG @ 100 °F
pH (neat):	Not Applicable	Vapor Density:	> 1.0 (Air = 1.0)
Viscosity:	~5 cst @ 100°F	Evaporation Rate:	22.6 (Butyl Acetate = 1.0)
Solubility:	Hydrocarbon Soluble		

Note: These physical properties are typical values for this product and not specifications.

8. Fire & Explosion Information

Flash Point:	<10°F
Lower Explosive Limit:	1.0%
Upper Explosive Limit:	50.0%

Extinguishing Media: Based on NFPA guide, use water fog, dry chemical, foam, carbon dioxide or other extinguishing agent suitable for Class B fires. Use water to cool containers exposed to fire. For large fires, use water spray or fog, thoroughly drench the burning material.

Unusual Fire And Explosion Hazards: May evolve CO, CO₂, NO_x and/or oxides of sulfur under fire conditions. Containers exposed in a fire should be cooled with water to prevent vapor pressure buildup leading to rupture.

9. Reactivity Information

Incompatibility: This product reacts incandescently with chemically active metals such as zinc, sodium and potassium. Contact with azides and inorganic acids can be explosive. Avoid contact with strong oxidizers (eg. chlorine, peroxides, chromates, nitric acid, perchlorates, concentrated oxygen, permanganates) which can generate heat, fires, explosions and the release of toxic fumes.

Thermal Decomposition Products: In the event of combustion CO, CO₂,NO_x, and oxides of sulfur may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment.

10. Personal Protection Equipment

Respiratory Protection: If it is possible to generate significant levels of vapors, mists or smoke, a NIOSH approved or equivalent respirator is recommended. For large spills, entry into large tanks, vessels or enclosed small spaces with inadequate ventilation, a positive pressure, self-contained breathing apparatus is recommended.

Ventilation: General ventilation is recommended. Additionally, local exhaust ventilation is recommended where vapors, mists or aerosols may be released.

Protective Equipment: Wear impermeable gloves, boots, apron and face shield with chemical splash goggles when attaching feeding equipment, doing maintenance or handling product. Viton gloves are recommended. A full slicker suit is recommended if gross exposure is possible.

The availability of an eye wash fountain and safety shower are recommended. If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse.

PCO-5450

Revision Date: January 17, 2011

Material Safety Data Sheet

Page 4 of 6

11. Spill & Disposal Information

In case of transportation accident, call the emergency response phone number: 800-535-5053

Spill Control And Recovery:

Immediately remove all sources of ignition from the spill area. Evacuate the area of all non-essential personnel. Those responsible for control and recovery should wear protective equipment specified in Section 10. Stop the source of the spill. Use only non-sparking tools.

Small Spills: Contain with absorbent material, such as clay, soil or any commercially available absorbent. Shovel reclaimed liquid and absorbent into recovery or salvage drums for disposal. Refer to CERCLA in Section 14.

Large Spills: Dike and prevent further movement and reclaim into recovery or salvage drums or tank truck for disposal. Refer to CERCLA in Section 14.

For large indoor spills, evacuate employees and ventilate area. Eliminate all sources of spark or flame. Those responsible for control and recovery should wear the protective equipment specified in Section 10. Ventilate area and evacuate employees from exposure if the airborne concentration exceeds the TLV. Refer to Section 14.

Prevent flow/discharge into lakes, ponds, streams, waterways or public water supplies.

Disposal: If this product becomes a waste, it meets the criteria of a hazardous waste as defined under the Resources Conservation and Recovery Act (RCRA) 40 CFR 261. Hazardous Waste D001.

As a hazardous liquid waste, it must be solidified with stabilizing agents (such as sand, fly ash, or cement) so that no free liquid remains before disposal to a licensed industrial waste landfill (Hazardous Waste Treatment, Storage and Disposal facility). A hazardous liquid waste can also be incinerated in accordance with local, state and federal regulations.

12. Environmental Information

If released into the environment, see CERCLA in Section 14.

13. Transportation Information

The proper shipping name and/or hazard class for this product may vary according to packaging, properties and mode of transportation. Typical proper shipping names for this product are:

All Transportation Modes:	Flammable Liquid, Toxic, N.O.S.
UN/ID Number:	UN-1993
Hazard Class:	3, Flammable Liquid
Packing Group:	II
Flash Point:	<10°F
Hazardous Components:	Carbon Disulfide, Xylene, Isopropanol, Light Hydrocarbon
RQ lbs:	165

RQ Component(s): Carbon Disulfide, Xylene

PCO-5450
Material Safety Data Sheet

Revision Date: January 17, 2011
Page 5 of 6

14. Regulatory Information

The following regulations apply to this product:

Federal Regulations:

OSHA's Hazard Communication Rule, 29 CFR 1910.1200:

Based on our hazard evaluation, the following ingredients in this product are hazardous and the reasons are shown below.

Carbon Disulfide – Systemic Effects, Flammable
Xylene – Eye irritant, Flammable
Isopropanol – Flammable
Light Hydrocarbon – Irritant, Combustible

Carbon Disulfide = TWA 20 ppm	OSHA/PEL
Carbon Disulfide = TWA 10 ppm	ACGIH/TLV
Xylene = TWA 100 ppm, STEL 125 ppm	OSHA/PEL
Xylene = TWA 100 ppm, STEL 125 ppm	ACGIH/TLV
Isopropanol = TWA 400 ppm, STEL 500 ppm	ACGIH/TLV
Isopropanol = TWA 400 ppm, STEL 500 ppm	OSHA/PEL
Light Hydrocarbon = TWA 14 ppm	NIOSH

CERCLA/Superfund, 40 CFR 117, 302:

This product contains carbon disulfide and xylene, Reportable Quantity (RQ) substances. If 165 pounds of this product is released it requires notification to the NATIONAL RESPONSE CENTER, WASHINGTON, D.C. at 800-424-8802.

SARA/Superfund Amendments And Reauthorization Act Of 1986

(Title III) – Sections 302, 311, 312 and 313:

Section 302 – Extremely Hazardous Substance (40 CFR 355):

This product contains the following ingredient(s) listed in Appendix A and B as Extremely Hazardous Substance(s).

Carbon Disulfide

Section 311 and 312 – Material Safety Data Sheet Requirements (40 CFR 370):

Our hazard evaluation has found this product to be hazardous. The product should be reported under the following EPA hazard categories.

***** Immediate (acute) health hazard
***** Delayed (chronic) health hazard
***** Fire hazard
***** Sudden release of pressure hazard
***** Reactive hazard

***** Indicates Primary Hazards

Under SARA 311 and 312, the EPA has established threshold quantities for the reporting of a hazardous chemical. The current thresholds are: 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

PCO-5450
Material Safety Data Sheet

Revision Date: January 17, 2011
Page 6 of 6

14. Regulatory Information (continued from page 5)

Section 313 – List Of Toxic Chemicals (40 CFR 372):

This product contains the following ingredient(s), (with CAS# and % range) which appear(s) on the List Of Toxic Chemicals:

Carbon Disulfide	75-15-0	Confidential
Xylene	1330-20-7	20%

Toxic Substance Control Act (TSCA) (40 CFR 710):

The chemical ingredients in this product are on the 8 (b) inventory list.

Resource Conservation Recovery Act (RCRA), 40 CFR 261 Subpart C & D:

Consult Section 11 for RCRA classification.

Federal Water Pollution Control Act, Clean Water Act, 40 CFR 401.15 (formerly Sec. 307), **40 CFR 116**, (formerly Sec. 311):

Xylene – Section 311

Clean Air Act, Sec 111 (40 CFR60), Sec 112 (40 CFR 61, 1990 Amendments), Sec 611 (40 CFR 82, Class I and II Ozone Depleting Substances):

Carbon Disulfide – Section 112
Xylene – Section 111
Isopropanol – Section 111

State Regulations:

California Proposition 65:

This product contains carbon disulfide which is known to the state of California to cause birth defects or other reproductive harm.

Michigan Critical Materials:

This product contains the following substances which are identified on the Michigan Critical Materials Register.

Carbon Disulfide
Xylene

State Right To Know Laws:

This product is regulated in those states using the TLV for carbon disulfide, xylene, isopropanol or light hydrocarbon as a criteria for listing.

15. User's Responsibility

The information accumulated herein is believed to be accurate based on the information provided, although no guarantee or warranty, either expressed or implied is made as to the accuracy or completeness of this information, whether originating with this company or not. Recipients are advised to confirm in advance of need that the information is correct, applicable and suitable to their circumstances. The conditions or methods of handling, storage, use and disposal of the product and container are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling,

storage or use of this information or product. If the product is used as a component in another product, this information may not be applicable.